



Excellent Design & Manufacture

## Pressure and Vacuum Detectors for Process Applications

### EDM pressure detectors

are rugged, field-mounted instruments. The pressure sensing element of the EDM pressure detector is a force-balance, piston-actuated assembly. The sensing element is sealed by a flexible diaphragm and a static o-ring. A wide selection of wetted parts materials for media compatibility and containment are available. A metal diaphragm may be welded to the pressure port for certain applications, thereby eliminating the o-ring.

### Application Information

The EDM pressure detectors in this catalog are suitable for a variety of process applications. Basic models with standard wetted parts are normally suitable for air, oil, water and non-corrosive processes. Certain applications may require customized specials. Consult the EDM representative in your area or the factory.



### Features and Benefits

#### Complete Product Line

- Standard models and customized specials cover pressure ranges from 30 inches Hg VAC to 4000 psi.

#### Robust Construction

- Rugged, high-cycle rate tolerance, long life, not critical to vibration, high overrange and proof pressures, excellent corrosion resistance to hostile environments.
- Enclosure ratings: NEMA 1, 4, 4X, 7, or 9 available.
- Ingress protection rating up to IP66.

#### Instrument Quality

- High resolution of set points, high repeatability, narrow dead band, negligible temperature effect.

#### Wetted Parts

- Wide selection materials, process connection configurations and sizes. Optional "fire-safe" pressure sensor.

#### Snap-Action Electrical Detecting

- Wide selection UL Listed and CSA Certified detecting elements for AC and DC service. Optional "hermetically sealed" capsule for hazardous and hostile environments.

#### Field Adjustable

- Self-locking adjustment, no special tools required. No-charge factory calibration.

#### Cost Effective

- Simple and fast installation without special tools, long service life, no required periodic service or spare parts.

#### Agency Listings/Certification

- Select models with ATEX, IECEx, CSA, FM, GOST R, INMETRO, Rostekhnadzor (RTN), TIIS, UL
- Meets most code and customer requirements.

#### Safety Certified to IEC 61508 (SIL)

- EDM products are certified to IEC 61508 for non-redundant use in SIL1 and SIL2 Safety Instrumented Systems for most models. For more details or values applicable to a specific product, see the Safety Integrity Level Quick Guide.

#### Shock/Vibration

- Select models tested to MIL-S-901D (Navy) shock test.
- Select models tested to MIL-S-167 vibration test.

#### Built-In Quality

- Rigid quality standards maintained from raw material to finished product.

#### Delivery

- Routine shipments 7 to 10 working days. Emergency shipments via same day air.

#### Service

- Factory sales engineers and area EDM representatives provide effective and prompt worldwide service.

## Model Number System

# EELP01-410024-410

| Adjustable Range |           | Typical Dead Band |     | Overrange |     | Proof |     |
|------------------|-----------|-------------------|-----|-----------|-----|-------|-----|
| psi              | bar       | psi               | bar | psi       | bar | psi   | bar |
| 200 to 1000      | 1.4 to 70 | 9.2               | 0.6 | 2500      | 170 | 6000  | 410 |

## Product Specifications

|                               |                      |                         |              |
|-------------------------------|----------------------|-------------------------|--------------|
| Housing                       |                      | Wetted Materials        |              |
| Weatherproof NEMA 4, 4X, IP66 |                      | Diaphragm               | 316L SS      |
| Electrical                    | 3/4" NPT(F) - Right  | O-Ring                  | Viton        |
| Material                      | Copper-free aluminum | Pressure Port           |              |
| Detecting Element             |                      | Process Connection Size | 1/4" NPT(F)  |
|                               |                      | Pressure Port Material  | 316SS/316LSS |
|                               | Designator           | SPDT                    |              |
|                               | Rating               | 5 Amps @ 30 VDC         |              |
| Dead Band Multiplier          | 1.0                  |                         |              |

## Weatherproof - NEMA 4, 4X, IP66

